



## CareSoft Elite® Cabinet Softeners

### Advanced efficiency for your home.

Our advanced CareSoft Elite Cabinet water softener goes above and beyond to refine the water for your home. Its convenient size is great for saving space while its high capacity resin media and patented self-chlorinating feature delivers a higher level of water quality.

The technology monitors your systems and allows a precise level of chlorine to pass through the media bed with each regeneration to keep your unit clean. The CareSoft Elite Cabinet features our exclusive Water Efficient Technology which fine-tunes the water and salt used to regenerate the media reducing waste.

The system is designed to be environmentally-friendly while safeguarding your household plumbing, appliances, skin, hair, and laundry. The result is good, quality water for your daily life.



### Efficiency is in the details.

Water Efficient Technology is our latest breakthrough in water treatment. W.E.T. is a series of patented features to reduce the amount of water and salt used.

- Regenerates with up to half the amount of water as a traditional system
- Does not waste salt during regeneration
- Salt alarm to notify you when more salt is needed
- Savings history screen keeps track of how much you save

No other water treatment solution can compare in performance to our W.E.T. features exclusive to WaterCare products. Put the most efficient system on the market in your home to save you water, salt, and money.

**Wripli** is the most advanced WiFi technology in water treatment today. Receive alerts, track water usage and view savings right from your phone, tablet or desktop. You can also activate "Vacation Mode" from anywhere in the world.



# Better treatment for better water.

Every component, feature, and innovation of our CareSoft Elite Cabinet softeners has been designed to bring the most efficient, highest quality water to you and your family. CareSoft Elite models are certified for compliance with NSF/ANSI 44.



## Exclusive Technology

- Deep cleaning regeneration only when necessary
- Exclusive features ensures consistent water quality
- Vacation Mode to prevent unnecessary regenerations while you're away
- Only one internal moving part for easy maintenance
- Battery back-up

## Equipped with W.E.T.

- **Proportional Brining:** uses less salt (*Available on Upflow Units Only*)
- **Proportional Regeneration:** uses less water
- **Alternate Regeneration:** keep the system running at peak performance
- **Salt Monitor:** triggers alarm when salt levels are low
- **Savings History Screen:** shows how much it saves



## Wripli Enabled (optional)

- **Current Flow Rate:** See how much treated water is running through your home in real time.
- **Water Usage:** Monitor the total number of gallons of water your home used during the day.
- **Savings:** See how much salt and water you have saved with W.E.T.
- **Notifications:** Receive notifications for salt reminders, service alarms and system errors.
- **Vacation Mode:** Set Vacation Mode from anywhere in the world.



## Patented Chlorine Generator

- Ability to self-clean unit
- Monitors every cleaning

## Quartz Underbedding

- Delivers high and consistent flow rates
- Provides accurate and efficient cleaning process

## High-Performance Resin

- Powerful and durable media
- Reduces the minerals that cause hard water
- Undergoes rigorous quality control testing

## Low-Maintenance Brine Tank

- Built-in safety float
- Heavy duty, corrosion-free material
- Fills with soft water which reduces cleaning
- Dry salt storage

## Making good water for your life.

### CABINET MODEL Specifications

MODEL		CSEC-835(U) <sup>2</sup>	CSEC-1035(U) <sup>2</sup>
Rated Softener Capacity: <sup>*</sup> (Grains/Lbs. Salt)	Minimum	5,100 @ 2.3	18,200 @ 4.5
	Medium	7,300 @ 6.0	23,500 @ 9.0
	Maximum	7,800 @ 7.5	28,000 @ 15.0
Amount of High Capacity Cat-ion Resin (Cu. Ft.)		.50	1.0
Efficiency at 1 lb Salt Setting (Grains/Lbs Salt)		N/A	4,040/1
Max. Service Flow Rate (GPM)		9.6	16.0
Max. Pressure Loss at Max. Service (PSI)		9.0	15.0
Min. to Max. Working Pressure (PSI)		30-100	30-100
Min. to Max. Operating Temperature (°F)		33-100	33-100
Max. Flow to Drain During Regeneration (GPM)		1.3	2.2
Electrical Requirements (volts-hertz)		110-50/60	110-50/60
Pipe Size		1"	1"
Total Dimensions:	<sup>1</sup> Cabinet	14"W x 44.5"H x 20.5"D	14"W x 44.5"H x 20.5"D

<sup>1</sup> Cabinet dimensions represent the High-Profile cabinet option. Low-Profile cabinets are about one inch shorter in height than the High-Profile cabinet lid.

<sup>2</sup> The "U" designation is for ordering upflow units only. Upflow units are not WQA certified.



Your local authorized WaterCare dealer:



© 2021 WaterCare All rights reserved. 3/23



phone: (517) 545-7517 • web: [adamswelldrilling.com](http://adamswelldrilling.com)

email: [info@adamswelldrilling.com](mailto:info@adamswelldrilling.com)

5893 Sterling Dr. Howell, MI 48843